

超塑烯® UE647-04

EVATHENE® UE647-04

乙烯醋酸乙烯酯共聚合樹脂

ETHYLENE-VINYL ACETATE COPOLYMER RESINS



概述

超塑烯® UE647-04 是一種乙烯醋酸乙烯酯共聚合樹脂。

Description

EVATHENE® UE647-04 is an ethylene-vinyl acetate copolymer resin (EVA).

特性

- ◇ 極高流動性
- ◇ 柔軟性
- ◇ 彈性
- ◇ 優異的熱穩定性
- ◇ 耐低溫性極佳
- ◇ 衛生無毒
- ◇ 與增黏劑樹脂及石蠟的兼容性佳

Characteristics

- ◇ High flowability
- ◇ Flexibility
- ◇ Elasticity
- ◇ Excellent heat stability
- ◇ Good low temperature resistance
- ◇ Non-toxicity
- ◇ Outstanding compatibility with tackifier resins and petroleum wax.

應用

配製熱熔膠

Applications

Hot melt adhesives

物理性質 Physical Properties

項目 Properties	試驗方法 Test Method	數 值 Typical Value
VA 含量 VA Content (%)	USI	28
熔融指數 Melt Index (g/10min)	ASTM D1238	800
密度 Density (g/cm ³)	ASTM D792	0.940
環球軟化溫度 Ring and Ball Softening Point (°C)	ASTM E28	80
熔點 Melt Point (°C)	ASTM D3418	63
硬度(蕭氏 A) Hardness (Shore A)	ASTM D2240	54

據本公司所知，上述資料應屬正確無誤，惟因使用時之情況非受本公司管制，所以本公司對上述所作之一切建議，恕不負保證之責。
The information contained herein is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all risks of such use are assumed by users.